

Product data sheet

WRB-5 *



Radio reception board for ECTurn, ECTurn Inside and Powerturn swing door drives

AREAS OF APPLICATION

- For insertion on the GEZE Powerturn, GEZE ECTurn and GEZE ECTurn Inside control unit
- Compatible with WTH remote control and WTM transmitting module
- Can be coupled with up to 12 WTH and/or WTM radio transmitters



PRODUCT FEATURES

- Encrypted communication via rolling code with up to 74 trillion code combinations
- Custom and reliable teach-in to exclude unauthorised activation
- Channel 1 for standard activation, press and hold to switch from the current mode of operation to hold open and back
- Channel 2 for push button/hand held transmitter with the function “authorised activation”

TECHNICAL DATA

Productname	WRB-5 *
Dimensions	44 x 27 x 10 mm
Operating current	7 mA
Type of installation	can be plugged in to DCU control units
Adjustability	with push of button
Transmission frequency	433.93 Mhz
Service temperature	-15 - 50 °C
Humidity	0-95 % relative, non-condensing

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	Operating voltage	Type of installation
Radio reception board WRB-5 *	for Powerturn, ECTurn and ECTurn Inside	135170	44 x 27 x 10 mm	5 V DC	can be plugged in to DCU control units

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.