

Product data sheet

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate



Sliding door fitting system for glass doors with a leaf weight of 140 kg and concealed wall bracket

AREAS OF APPLICATION

- Frequently used interior sliding doors
- Living, office, and conference areas as well as hotels
- Installation of fittings in all visible areas
- For elegant room design
- Visible attachment
- Single and double leaf sliding doors

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate

PRODUCT FEATURES

- Sliding door fitting for leaf weights of up to 140 kg
- For glass leaves with 45 mm clamping plates
- The Perlan track is screwed into the wall bracket from below, therefore covering the otherwise visible fixings when in an installed state
- Spacer profiles enable quick compensation of the interval between the track and protruding frames or foot ledge profiles
- With damping on one or both sides for doors with up to 80 kg leaf weight, so that the door is quietly slowed down and moved into the end position
- Precision ball bearings in the roller carriages offer very smooth sliding action
- Tested for durability in accordance with DIN EN 1527 over 100,000 test cycles

TECHNICAL DATA

Productname	Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate
-------------	---

PART

PERLAN 140 SET FOR GLASS LEAVES

Sliding door fitting for wall installation and glass leaf



Designation	Description	Ident-No.	Colour	Leaf width (min.)	Leaf width (max.)
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. / For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134860	Stainless steel optic	575 mm	1000 mm
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. / For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134855	EV1	900 mm	1240 mm
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. / For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134861	Stainless steel optic	900 mm	1240 mm
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. / For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134854	EV1	575 mm	1000 mm

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate



ACCESSORIES

END STOP WITH ADJUSTABLE HOLD-OPEN SPRING

Adjustable end stop for Perlan sliding door fitting



Designation	Ident-No.
End stop with adjustable hold-open spring	069274

HOLD-OPEN SPRING

Hold-open spring for Perlan 140 end stop



Designation	Ident-No.
Hold-open spring	064242

DOOR STOP

End stop for sliding leaves



Designation	Ident-No.
Door stop	000339
Door stop	000342

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate



LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 5x1 g *	for up to 5 sliding panels	133056

CLAMPING INSERT, GLASS CLAMPING PLATE 45 MM *

Clamping shim for glass thicknesses of 12.76 mm (1/2 inch)



Designation	Description	Ident-No.
Clamping insert, glass clamping plate 45 mm *	for 2 glass clamping plates, for use with 12.7 mm (1/2 inch) toughened safety glass	133022

PERLAN DUOSYNC SET FOR GLASS LEAVES

Duosync - manual drive for glass leaves



Designation	Description	Ident-No.	Glass thickness	Type of installation
Perlan Duosync set for glass leaves	for synchronisation of 2-leaf doors up to 140 kg per leaf, consisting of: 2 x deflection pulleys, 2 x driver glass clamping plate 45 mm, 12.5 m tooth belt, installation materials	139207	8 - 12.76 mm	Wall, Ceiling

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate



PERLAN SOFTSTOP SET, MEDIUM VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 900 up to 1290 mm



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, medium, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128877	900 mm	1290 mm

PERLAN SOFTSTOP SET, LONG VERSION, DAMPED ON BOTH SIDES, UP TO 80 KG

Perlan SoftStop damping on both sides for leaf weights up to 80 kg



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, long, both sides	The set includes: 2 x roller carriage with damping unit on both sides, 2 x end stop, 2 x trigger with fixing screws, 2 x standard suspension plate	128891	1290 mm	1700 mm

SET PERLAN SOFTSTOPDUO, DAMPED ON BOTH SIDES

Perlan SoftStopDuo with damping on both sides up to 80 kg leaf weight



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStopDuo set, damped on both sides, up to 80 kg	The set includes: 2 x roller carriage with damping unit on both sides, 2 x end stop, 2 x trigger with fixing screws, 2 x standard suspension plate	150071	750 mm	1290 mm

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate



LSG GLUEING BRACKET SET *

Aluminium glueing bracket for LSG and glass clamping plate 45



Designation	Description	Ident-No.
LSG glueing bracket set *	for use with LSG in connection with glass clamping plate 45 mm, for 2 clamping plates, without adhesive	133099

DOOR PULL HANDLE, CONFIGURED *

Push bar – round design for installation on glass leaves



Designation	Ident-No.	Colour
Door pull handle, configured *	127616	Stainless steel

PERLAN SOFTSTOP SET, SHORT VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 575 to 900 mm



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, short, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128876	575 mm	900 mm

Perlan 140 glass concealed wall bracket with 45 mm glass clamping plate



FLOOR GUIDE SET GLASS GUIDE

Floor guide for glass sliding leaves for glass thickness 8, 10 and 12 mm



Designation	Description	Ident-No.	Colour	Glass thickness
Floor guide for glass leaf (stainless steel)	For 8, 10, 12 mm glass	134990	Stainless steel	8 - 12 mm

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.